

Minimate Plus™

Advanced Vibration and Overpressure Monitor

Range of Applications:

- Blast-monitoring for compliance
- Near-field blast analysis
- Pile driving
- Construction activity
- Demolition activity
- Heavy Transportation
- Bridge monitoring
- Structural analysis
- Underwater blast monitoring
- 4 or 8 channel data acquisition
- Remote monitoring - Auto Call Home™
- Structural monitoring - Flex™

When we asked what you wanted in a vibration monitor, you said “Everything.” So, we designed the **InstanTel® Minimate Plus™** vibration and overpressure monitor. Ever since, it has become a favourite of contractors, consultants, engineers and blasters, because it offers unrivalled features and versatility in a rugged and easy-to-use package.

Versatile

Use the **Minimate Plus** monitor with an **InstanTel Standard Triaxial Geophone** (ISEE or DIN version) and an overpressure microphone (Linear or A Weight) to provide a rugged, reliable compliance monitoring system. Add the **InstanTel 8-Channel** option and a single monitor may be used with two triaxial geophones and two microphones.

For more demanding monitoring applications, the **InstanTel Blastware® Advanced Module** software provides the capability to monitor a broad selection of vibration and overpressure sensors, as well as sensors for structural and environmental measurements. Monitor vibration, ambient environmental conditions, and the movement of structural cracks, all at the same time, all using the same **Minimate Plus** monitor.

Intelligent

For remote installations, the **InstanTel Auto Call Home™** feature will automatically transfer event files from field to office as they are recorded using a variety of wired or wireless modems. From there, the **Blastware Mail** feature of the **Blastware** software automatically distributes files or summary information to multiple e-mail or text messaging addresses.

Easy to use

Even with all of these features, the **Minimate Plus** system is still easy for anyone to use. A high-contrast LCD, eight-key tactile keypad, coupled with simple menu-driven operations, provides complete control and confidence.

Minimate Plus - everything you need and more.



Key Features

- **InstanTel Histogram Combo™** mode allows capture of full waveform records while recording in histogram mode.
- **Auto Call Home** feature automates remote monitoring applications.
- Sample rates from 1,024 to 4,096 S/s, per channel with up to 65,000 S/s available on a single channel.
- Available **InstanTel 8-channel** option allows for two standard geophones and two microphones to be operated from one **Minimate Plus** monitor.
- Non-volatile memory with standard 300-event storage capacity (optional 1,500-event capacity).
- Records waveform events up to 100 seconds long with standard setup, or up to 500 seconds with advanced setup.
- Continuous monitoring means zero dead time, even while the unit is processing.
- Any channel can be matched to a wide variety of sensors - geophones, accelerometers, or hydrophones.

Minimate Plus™

General Specifications

Minimate Plus

Channels	Microphone and Triaxial Geophone or 4 independent user-configurable channels (two Microphones and two Triaxial Geophones or 8 independent channels with optional 8-channel upgrade)
Vibration Monitoring (with Standard Triaxial Geophone)	
Range	Up to 254 mm/s (10 in/s)
Resolution	0.127 mm/s (0.005 in/s) or 0.0159 mm/s (0.000625 in/s) with built-in preamp
Accuracy (ISEE / DIN)	+/- 5% or 0.5 mm/s (0.02 in/s), whichever is larger, between 4 and 125 Hz / DIN 45669-1 standard
Transducer Density	2.13 g/cc (133 lbs/ft ³)
Frequency Range (ISEE / DIN)	2 to 250 Hz, within zero to -3 dB of an ideal flat response / 1 to 315 Hz
Maximum Cable Length (ISEE / DIN)	75 m (250 ft) / 1,000 m (3,280 ft)
Air Overpressure Monitoring	
Weighting Scales	Linear or A-weight
Linear Range	88 to 148 dB (500 Pa (0.072 PSI) Peak)
Linear Resolution	0.25 Pa (0.0000363 PSI)
Linear Accuracy	+/- 10% or +/- 1 dB, whichever is larger, between 4 and 125 Hz
Linear Frequency Response	2 to 250 Hz between -3 dB roll off points
A-Weight	
A-weight Range	50 to 110 dBA
A-weight Resolution	0.1 dBA
A-weight Frequency Response	15 to 8,000 Hz

Waveform Recording

Record Modes	Manual, Single-shot, Continuous
Seismic Trigger	0.127 to 254 mm/s (0.005 to 10 in/s)
Acoustic Triggers	
Linear	100 to 148 dB
A-weight	55 to 110 dBA
Sample Rate	1,024 to 4,096 S/s per channel (independent of record time), up to 65,536 S/s in single-channel mode with advanced software (max 8,192 S/s per channel for 8 channels)
Record Stop Mode	Fixed record time, Instantel® AutoRecord™ record stop mode
Record Time	1 to 100 seconds (programmable in one-second steps), or advanced mode, 500 seconds plus 0.25 seconds
AutoRecord Time	pre-trigger Auto window programmable from 1 to 9 seconds, plus a 0.25 second pre-trigger. Event is recorded until activity remains below trigger level for duration of auto window, or until available memory is filled. Recording uninterrupted by event processing - no dead time
Cycle Time	
Storage Capacity	
Full Waveform Events	300 one-second events at 1,024 S/s sample rate (1,500 event capacity with optional memory upgrade)
Event Summaries	1,750 (8,750 event capacity with optional memory upgrade)

Histogram Recording

Record Modes	Histogram and Instantel Histogram Combo™ (monitor captures triggered waveforms while recording in Histogram mode)
Recording Interval	2, 5 or 15 seconds; 1, 5 or 15 minutes
Storage Capacity	46,656 intervals - 3 days at 5-second intervals or 486 days at 15-minute intervals (with memory upgrade - 15 days at 5-second intervals or 540 days at 15-minute intervals)

Physical Specifications

Dimensions	81 x 91 x 160 mm (3.2 x 3.6 x 6.3 in)
Weight	1.4 kg (3 lbs)
Battery	Rechargeable 6 V sealed gel cell - capacity for 210 hours of continuous monitoring
User Interface	8-key keypad with domed tactile keys
Display	4-line x 20-character, high-contrast, backlit LCD
PC Interface	RS-232
Auxillary Inputs and Outputs	External Trigger, Remote Alarm, coordinate download from GPS
Environmental	
LCD Operating Temperature	-10 to 50°C (14 to 122°F)
Electronics Operating Temperature	-20 to 55°C (-4 to 131°F)
Remote Communications	Compatible with Telephone, GSM, Cellular, RF, Satellite, Short-haul modems and Ethernet® device servers. Automatically transfers events when they occur through the Instantel Auto Call Home™ feature.
Additional Features	Monitor start/stop timer
Electrical Standards	CE Class A

Corporate Office:
309 Leggett Drive,
Ottawa, Ontario K2K 3A3
Canada

US Office:
808 Commerce Park Drive,
Ogdensburg, New York 13669
USA

Toll Free: (800) 267 9111
Telephone: (613) 592 4642
Facsimile: (613) 592 4296
Email: sales@instantel.com



© 2013 Xmark Corporation. Instantel, the Instantel logo, Auto Call Home, AutoRecord, Blastmate, Blastware, Histogram Combo, InstaLink, and Minimate are trademarks of Stanley Black & Decker, Inc., or its affiliates.

StanleyBlack&Decker

714B0052 Rev 09 - Product Specifications are Subject to Change

The World's Most Trusted Vibration Monitors